



PRODUCT-DETAILS

3GBA092510-ASC

M2BAX 90LA 4

General Information

Product ID	3GBA092510-ASC
ABB Type Designation	M2BAX 90LA 4
Catalog Description	M2BAX 90LA 4

Additional Information

ABB Type Designation	M2BAX 90LA 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	China (CN) Poland (PL)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	1.50 kW	1441 r/min	3.58 A	0.730	82.80 %	10.00 N·m	6.90
D	--	50 Hz	230 V	1.50 kW	1441 r/min	6.20 A	0.730	82.80 %	10.00 N·m	6.90
Y	--	50 Hz	380 V	1.50 kW	1435 r/min	3.55 A	0.770	82.80 %	10.00 N·m	6.60
D	--	50 Hz	220 V	1.50 kW	1435 r/min	6.15 A	0.770	82.80 %	10.00 N·m	6.60
Y	--	60 Hz	440 V	1.50 kW	1748 r/min	3.20 A	0.730	84.00 %	8.25 N·m	7.80
Y	--	60 Hz	460 V	1.50 kW	1754 r/min	3.24 A	0.700	84.00 %	8.23 N·m	8.10

Gross Weight 27 kg

IC Class IC411

IE Class Data (50 Hz) IE Class IE2
Full Load (100%) 82.8 %
Partial Load (75%) 81.6 %
Partial Load (50%) 78.4 %

IE Class Data (60 Hz) IE Class IE2
Full Load (100%) 84.0 %
Partial Load (75%) 82.4 %
Partial Load (50%) 78.7 %

IM Class IMB3 IM1001

IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2BAX 90LA 4
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	24 kg
Product Type	EBA2__M2BAX_CI
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC_60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Central Stock Europe CSCNM
Temperature Class Default	--
Temperature Rise	80 K
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)