



PRODUCT-DETAILS

3GBA093510-ASC

M2BAX 90LA 6

General Information

Product ID	3GBA093510-ASC
ABB Type Designation	M2BAX 90LA 6
Catalog Description	M2BAX 90LA 6

Additional Information

ABB Type Designation	M2BAX 90LA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	China (CN) Poland (PL)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	1.10 kW	936 r/min	3.17 A	0.650	78.10 %	11.06 N·m	4.60
D	--	50 Hz	230 V	1.10 kW	936 r/min	5.49 A	0.650	78.10 %	11.06 N·m	4.60
Y	--	50 Hz	380 V	1.10 kW	926 r/min	3.14 A	0.690	78.10 %	11.10 N·m	4.40
D	--	50 Hz	220 V	1.10 kW	926 r/min	5.44 A	0.700	78.10 %	11.10 N·m	4.40
Y	--	60 Hz	440 V	1.10 kW	1137 r/min	2.82 A	0.650	75.00 %	9.22 N·m	5.10
Y	--	60 Hz	460 V	1.10 kW	1143 r/min	2.86 A	0.610	75.00 %	9.18 N·m	5.30

Gross Weight	28 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 78.1 % Partial Load (75%) 76.2 % Partial Load (50%) 72.7 %
IE Class Data (60 Hz)	IE Class IE1 Full Load (100%) 75.0 % Partial Load (75%) 71.5 % Partial Load (50%) 65.8 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2BAX 90LA 6

Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	25 kg
Product Type	EBA2__M2BAX_CI
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC_60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Central Stock Europe CSCNM
Temperature Class Default	--
Temperature Rise	80 K
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)