
PRODUCT-DETAILS

3GBA203420-BDC

M2BAX 200MLB 6



General Information

Product ID	3GBA203420-BDC
ABB Type Designation	M2BAX 200MLB 6
Catalog Description	M2BAX 200MLB 6

Additional Information

ABB Type Designation	M2BAX 200MLB 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6212-2Z/C3
Bearing NDE	6209-2Z/C3
Country of Origin	China (CN) Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	22.00 kW	978 r/min	26.30 A	0.760	90.90 %	215.30 N·m	6.20
D	--	50 Hz	400 V	22.00 kW	978 r/min	45.60 A	0.760	90.90 %	215.30 N·m	6.20
Y	--	50 Hz	660 V	22.00 kW	974 r/min	26.90 A	0.790	90.90 %	215.90 N·m	5.70
D	--	50 Hz	380 V	22.00 kW	974 r/min	46.60 A	0.790	90.90 %	215.90 N·m	5.70
D	--	60 Hz	440 V	22.00 kW	1177 r/min	40.70 A	0.770	91.70 %	178.55 N·m	6.60
D	--	60 Hz	460 V	22.00 kW	1179 r/min	40.00 A	0.750	91.70 %	178.22 N·m	7.00

Gross Weight	229 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 90.9 % Partial Load (75%) 91.1 % Partial Load (50%) 90.5 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 91.7 % Partial Load (75%) 91.3 % Partial Load (50%) 90.3 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2BAX 200MLB 6
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	219 kg
Product Type	EBA2_M2BAX_CI
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC_60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Central Stock Europe
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Cast Iron Motors

