


PRODUCT-DETAILS

3GBP132270-BDK

IE3 Premium Efficiency Cast Iron Motor, 7.5 kW, 400 V (3GBP132270-BDK)



General Information

Product ID	3GBP132270-BDK
ABB Type Designation	M3BP 132SMG 4
Catalog Description	IE3 Premium Efficiency Cast Iron Motor, 7.5 kW, 400 V (3GBP132270-BDK)

Additional Information

ABB Type Designation	M3BP 132SMG 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Connection Configuration	D
Country of Origin	Finland (FI) China (CN) Poland (PL)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	7.50 kW	1464 r/min	8.50 A	0.810	90.40 %	48.90 N-m	7.70
D	--	50 Hz	400 V	7.50 kW	1464 r/min	14.70 A	0.810	90.40 %	48.90 N-m	7.70
Y	--	50 Hz	660 V	7.50 kW	1456 r/min	8.80 A	0.830	90.40 %	49.10 N-m	7.10
D	--	50 Hz	380 V	7.50 kW	1456 r/min	15.30 A	0.830	90.40 %	49.10 N-m	7.10
D	--	50 Hz	415 V	7.50 kW	1465 r/min	14.40 A	0.790	90.40 %	48.80 N-m	8.20
D	--	60 Hz	460 V	7.50 kW	1766 r/min	13.00 A	0.790	91.70 %	40.50 N-m	8.70

Frame Material	Cast Iron
Frame Size	132
Frequency (f)	50 Hz
Gross Weight	86 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 90.4 % Partial Load (75%) 90.5 % Partial Load (50%) 90.2 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 91.7 % Partial Load (75%) 91.6 % Partial Load (50%) 90.8 %
IM Class	IMB5 IM3001
Input Voltage (U _{in})	400 V
Insulation Class	ICLF
Invoice Description	M3BP 132SMG 4
IP Class	IP55
Made To Order	No
Medium Description	7.5kW, 4 Poles, Frame Size 132, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB5/IM3001 Mounting (3GBP132270-BDK)
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Output Power	7.5 kW
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Depth / Length	532 mm
Product Net Height	300 mm
Product Net Weight	81 kg
Product Net Width	262 mm
Product Type	3BP3_M3BP_IE3_CI
Quote Only	No
Replaced Product ID (OLD)	3GBP132270-BPK 3GBP132250-BDL
SCIP	54c45c7b-7581-40ab-b615-c1dcb277d8a7 Finland (FI)
Selling Unit of Measure	piece
Short Description	7.5kW, 4P, Frame Size 132, 3PH, 400V, 50Hz, IP55, IMB5/IM3001
Stocked At (Warehouses)	Menden, Germany Shanghai, China
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1

UNSPSC

26101100
39120000

Voltage Code

D

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Cast Iron Motors

