


PRODUCT-DETAILS

3GGP093570-BSK

Dust Ignition Proof IE3 LV Motors, 0.75 kW,
400 V (3GGP093570-BSK)



General Information

Product ID	3GGP093570-BSK
ABB Type Designation	M3GP 90LG 6
Catalog Description	Dust Ignition Proof IE3 LV Motors, 0.75 kW, 400 V (3GGP093570-BSK)

Additional Information

ABB Type Designation	M3GP 90LG 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Connection Configuration	Y
Country of Origin	Finland (FI)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	400 V	0.75 kW	938 r/min	1.80 A	0.740	78.90 %	7.70 N-m	4.80
D	T3	50 Hz	230 V	0.75 kW	938 r/min	3.10 A	0.740	78.90 %	7.70 N-m	4.80
Y	T3	50 Hz	380 V	0.75 kW	927 r/min	1.86 A	0.760	78.90 %	7.70 N-m	4.30
D	T3	50 Hz	220 V	0.75 kW	927 r/min	3.20 A	0.760	78.90 %	7.70 N-m	4.30
Y	T3	50 Hz	415 V	0.75 kW	943 r/min	1.74 A	0.730	78.90 %	7.70 N-m	5.10
Y	T3	60 Hz	460 V	0.75 kW	1146 r/min	1.60 A	0.720	82.50 %	6.30 N-m	5.50

EX-Protection	Exec
Frame Material	Cast Iron
Frame Size	90
Frequency (f)	50 Hz
Gas Group	IIC
Gross Weight	37 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 78.9 % Partial Load (75%) 79.9 % Partial Load (50%) 78.6 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 82.5 % Partial Load (75%) 82.5 % Partial Load (50%) 80.1 %
IM Class	IMB5 IM3001
Input Voltage (U _{in})	400 V
Insulation Class	ICLF
IP Class	IP55
Made To Order	No
Medium Description	0.75kW, 6 Poles, Frame Size 90, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB5/IM3001 Mounting (3GGP093570-BSK)
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Output Power	0.75 kW
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Depth / Length	390 mm
Product Net Height	219 mm
Product Net Weight	34 kg
Product Net Width	177 mm
Product Type	3GP3_M3GP_IE3_CI
Quote Only	No
Selling Unit of Measure	piece
Short Description	0.75kW, 6P, Frame Size 90, 3PH, 400V, 50Hz, IP55, IMB5/IM3001
Temperature Class Default	T3
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors

