


PRODUCT-DETAILS

3GGP132250-BDL

Dust Ignition Proof IE3 LV Motors, 7.5 kW, 400 V (3GGP132250-BDL)



General Information

| | |
|----------------------|---|
| Product ID | 3GGP132250-BDL |
| ABB Type Designation | M3GP 132SME 4 |
| Catalog Description | Dust Ignition Proof IE3 LV Motors, 7.5 kW, 400 V (3GGP132250-BDL) |

Additional Information

| | |
|--------------------------|---------------|
| ABB Type Designation | M3GP 132SME 4 |
| Altitude | 1000 m |
| Ambient Temperature | 40 °C |
| Bearing | 6208-2Z/C3 |
| Bearing NDE | 6208-2Z/C3 |
| Connection Configuration | D |
| Country of Origin | Finland (FI) |
| Customs Tariff Number | 85015220 |
| Direction of Rotation | Both sides |
| Electrical Data | |

| Conn | Temp Class | Freq | Voltage | Power | Speed | Current | Power Factor | Efficiency | Torque | IS/IN |
|------|------------|-------|---------|---------|------------|---------|--------------|------------|-----------|-------|
| Y | T3 | 50 Hz | 690 V | 7.50 kW | 1462 r/min | 9.00 A | 0.760 | 90.40 % | 49.00 N-m | 7.90 |
| D | T3 | 50 Hz | 400 V | 7.50 kW | 1462 r/min | 15.70 A | 0.760 | 90.40 % | 49.00 N-m | 7.90 |
| D | T3 | 50 Hz | 415 V | 7.50 kW | 1464 r/min | 16.50 A | 0.700 | 90.40 % | 49.00 N-m | 8.30 |

| | |
|----------------------------------|---|
| EX-Protection | Exec |
| Frame Material | Cast Iron |
| Frame Size | 132 |
| Frequency (f) | 50 Hz |
| Gas Group | IIC |
| Gross Weight | 83 kg |
| IC Class | IC411 |
| IE Class Data (50 Hz) | IE Class IE3 Full Load (100%) 90.4 % Partial Load (75%) 90.5 % Partial Load (50%) 89.3 % |
| IE Class Data (60 Hz) | IE Class IE2 Full Load (100%) 89.5 % Partial Load (75%) 89.2 % Partial Load (50%) 87.5 % |
| IM Class | IMB5 IM3001 |
| Input Voltage (U _{in}) | 400 V |
| Insulation Class | ICLF |
| Invoice Description | M3GP 132SME 4 |
| IP Class | IP55 |
| Made To Order | No |
| Medium Description | 7.5kW, 4 Poles, Frame Size 132, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB5/IM3001 Mounting (3GGP132250-BDL) |
| Minimum Order Quantity | 1 piece |
| Number of Poles (High) | 4 |
| Order Multiple | 1 piece |
| Output Power | 7.5 kW |
| Package Level 1 Units | 0 carton |
| Product Name | 3-Phase squirrel cage motor |
| Product Net Depth / Length | 533 mm |
| Product Net Height | 300 mm |
| Product Net Weight | 78 kg |
| Product Net Width | 273 mm |
| Product Type | 5GP3 M3GP CI |
| Quote Only | No |
| Selling Unit of Measure | piece |
| Short Description | 7.5kW, 4P, Frame Size 132, 3PH, 400V, 50Hz, IP55, IMB5/IM3001 |
| Temperature Class Default | T3 |
| Terminator Box Location | D-End top |
| Two Speed Motor | No |
| Type of Duty | S1 |
| UNSPSC | 26101100 |
| Voltage Code | D |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors

