


PRODUCT-DETAILS

3GGP134102-BSB

M3GP 132SMB 8



General Information

Product ID	3GGP134102-BSB
ABB Type Designation	M3GP 132SMB 8
Catalog Description	M3GP 132SMB 8

Additional Information

ABB Type Designation	M3GP 132SMB 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	400 V	3.00 kW	715 r/min	8.50 A	0.640	79.90 %	39.70 N·m	4.70
D	T3	50 Hz	230 V	3.00 kW	715 r/min	14.80 A	0.640	79.90 %	39.70 N·m	4.70
Y	T3	60 Hz	460 V	3.00 kW	870 r/min	6.90 A	0.650	83.20 %	32.75 N·m	5.20

EX-Protection	Exec
Frame Material	Cast Iron
Frame Size	132

Gas Group	IIC
Gross Weight	80 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE1 Full Load (100%) 79.9 % Partial Load (75%) 79.7 % Partial Load (50%) 76.6 %
IE Class Data (60 Hz)	IE Class IE1 Full Load (100%) 83.2 % Partial Load (75%) 82.0 % Partial Load (50%) 78.4 %
IM Class	IMB5 IM3001
Insulation Class	ICLF
Invoice Description	M3GP 132SMB 8
IP Class	IP55
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	75 kg
Product Type	3GP0__M3GP_CI
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Temperature Class Default	T3
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE2 LV motors

