
PRODUCT-DETAILS

3GGP161410-ADD

M3GP 160MLA 2



General Information

Product ID	3GGP161410-ADD
ABB Type Designation	M3GP 160MLA 2
Catalog Description	M3GP 160MLA 2

Additional Information

ABB Type Designation	M3GP 160MLA 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6309/C3
Bearing NDE	6209/C3
Country of Origin	Finland (FI) Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
EX-Protection	Exec
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Efficiency	Torque	IS/IN Factor
Y	T3	50 Hz	690 V	11.00 kW	2931 r/min	11.70 A	0.890 90.10 %	35.81 N·m	6.70
D	T3	50 Hz	400 V	11.00 kW	2931 r/min	20.20 A	0.890 90.10 %	35.81 N·m	6.70
D	T3	50 Hz	415 V	11.00 kW	2936 r/min	20.00 A	0.860 89.90 %	35.80 N·m	7.10

Gas Group	IIC
Gross Weight	149 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 89.9 % Partial Load (75%) 90.1 % Partial Load (50%) 88.9 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 160MLA 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	139 kg
Product Type	3GP0__M3GP_CI
Quote Only	No
Selling Unit of Measure	piece
Stocked At (Warehouses)	Central Stock Europe
Temperature Class Default	T3
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE2 LV motors

