

PRODUCT-DETAILS

3GGP203420-ADK**Dust Ignition Proof IE3 LV Motors, 22 kW, 400 V (3GGP203420-ADK)****General Information**

Product ID	3GGP203420-ADK
ABB Type Designation	M3GP 200MLB 6
Catalog Description	Dust Ignition Proof IE3 LV Motors, 22 kW, 400 V (3GGP203420-ADK)

Additional Information

ABB Type Designation	M3GP 200MLB 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6312/C3
Bearing NDE	6210/C3
Connection Configuration	D
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	690 V	22.00 kW	990 r/min	24.90 A	0.790	92.20 %	212.00 N-m	7.80
D	T3	50 Hz	400 V	22.00 kW	990 r/min	43.00 A	0.790	92.20 %	212.00 N-m	7.80
Y	T3	50 Hz	660 V	22.00 kW	988 r/min	25.20 A	0.820	92.20 %	212.00 N-m	7.20
D	T3	50 Hz	380 V	22.00 kW	988 r/min	43.70 A	0.820	92.20 %	212.00 N-m	7.20
D	T3	50 Hz	415 V	22.00 kW	991 r/min	43.20 A	0.760	92.20 %	212.00 N-m	8.10
D	T3	60 Hz	460 V	22.00 kW	1191 r/min	37.70 A	0.780	93.00 %	176.00 N-m	8.80

EX-Protection	Exec
Frame Material	Cast Iron
Frame Size	200
Frequency (f)	50 Hz
Gas Group	IIC
Gross Weight	328 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 92.2 % Partial Load (75%) 92.5 % Partial Load (50%) 91.6 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 93.0 % Partial Load (75%) 93.0 % Partial Load (50%) 91.8 %
IM Class	IMB3 IM1001
Input Voltage (U _{in})	400 V
Insulation Class	ICLF
Invoice Description	M3GP 200MLB 6
IP Class	IP55
Made To Order	No
Medium Description	22kW, 6 Poles, Frame Size 200, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB3/IM1001 Mounting (3GGP203420-ADK)
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Output Power	22 kW
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Depth / Length	822 mm
Product Net Height	528 mm
Product Net Weight	318 kg
Product Net Width	413 mm
Product Type	3GP3_M3GP_IE3_CI
Quote Only	No
Replaced Product ID (OLD)	3GGP203440-ADK
Selling Unit of Measure	piece
Short Description	22kW, 6P, Frame Size 200, 3PH, 400V, 50Hz, IP55, IMB3/IM1001
Standards	IEC 60034-1
Temperature Class Default	T3
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1

UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors

