


PRODUCT-DETAILS

# 3GGP311210-BDG

## M3GP 315SMA 2



### General Information

Product ID	3GGP311210-BDG
ABB Type Designation	M3GP 315SMA 2
Catalog Description	M3GP 315SMA 2

### Additional Information

ABB Type Designation	M3GP 315SMA 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6316/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015381
Direction of Rotation	Both sides

#### Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	690 V	110.00 kW	2982 r/min	112.00 A	0.860	94.90 %	352.00 N-m	7.40
D	T3	50 Hz	400 V	110.00 kW	2982 r/min	197.00 A	0.860	94.90 %	352.00 N-m	7.40
D	T3	50 Hz	415 V	110.00 kW	2983 r/min	192.00 A	0.850	94.90 %	352.00 N-m	8.10

Frame Material	Cast Iron
Frame Size	315
Gas Group	IIC
Gross Weight	900 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 94.9 % Partial Load (75%) 94.4 % Partial Load (50%) 92.9 %
IM Class	IMB5 IM3001
Insulation Class	ICLF
Invoice Description	M3GP 315SMA 2
IP Class	IP55
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Output Power	110 kW
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	880 kg
Product Type	3GP2_M3GP_IE2_CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	T3
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100 39120000
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

## Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE2 LV motors

Motors and Generators → Motors and Generators for Explosive Atmospheres → Increased Safety Ex ec Zone 2 Motors → Increased Safety IE2 Ex ec Motors

