


PRODUCT-DETAILS

# 3GGP351820-BDG

## M3GP 355LKB 2



### General Information

Product ID	3GGP351820-BDG
ABB Type Designation	M3GP 355LKB 2
Catalog Description	M3GP 355LKB 2

### Additional Information

ABB Type Designation	M3GP 355LKB 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6316M/C3
Bearing NDE	6316M/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015394
Direction of Rotation	Both sides

### Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	690 V	560.00 kW	2983 r/min	535.00 A	0.900	95.00 %	1792.00 N-m	8.00
D	T3	50 Hz	400 V	560.00 kW	2983 r/min	925.00 A	0.900	95.00 %	1792.00 N-m	8.00
D	T3	50 Hz	415 V	560.00 kW	2984 r/min	891.00 A	0.900	95.00 %	1792.00 N-m	8.60

EX-Protection	Exec
Frame Material	Cast Iron
Frame Size	355

Gas Group	IIC
Gross Weight	2490 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 95.0 % Partial Load (75%) 94.8 % Partial Load (50%) 93.8 %
IM Class	IMB5 IM3001
Insulation Class	ICLF
Invoice Description	M3GP 355LKB 2
IP Class	IP55
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Output Power	560 kW
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	2460 kg
Product Type	3GP2_M3GP_IE2_CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	T3
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

## Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE2 LV motors

Motors and Generators → Motors and Generators for Explosive Atmospheres → Increased Safety Ex ec Zone 2 Motors → Increased Safety IE2 Ex ec Motors

