


PRODUCT-DETAILS

3GGP353220-ADG

M3GP 355SMB 6



General Information

Product ID	3GGP353220-ADG
ABB Type Designation	M3GP 355SMB 6
Catalog Description	M3GP 355SMB 6

Additional Information

ABB Type Designation	M3GP 355SMB 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6322/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015381
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	690 V	200.00 kW	993 r/min	211.00 A	0.830	95.70 %	1923.00 N-m	7.20
D	T3	50 Hz	400 V	200.00 kW	993 r/min	364.00 A	0.830	95.70 %	1923.00 N-m	7.20
D	T3	50 Hz	415 V	200.00 kW	994 r/min	356.00 A	0.820	95.70 %	1921.00 N-m	7.50

Frame Material	Cast Iron
Frame Size	355
Gas Group	IIC
Gross Weight	1710 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 95.7 % Partial Load (75%) 95.7 % Partial Load (50%) 95.1 %
IM Class	IMB3 IM1001
Insulation Class	ICLF
Invoice Description	M3GP 355SMB 6
IP Class	IP55
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Output Power	200 kW
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	1680 kg
Product Type	3GP2_M3GP_IE2_CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	T3
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE2 LV motors

Motors and Generators → Motors and Generators for Explosive Atmospheres → Increased Safety Ex ec Zone 2 Motors → Increased Safety IE2 Ex ec Motors

