


PRODUCT-DETAILS

# 3GGP354420-ADG

## M3GP 355MLB 8



### General Information

Product ID	3GGP354420-ADG
ABB Type Designation	M3GP 355MLB 8
Catalog Description	M3GP 355MLB 8

### Additional Information

ABB Type Designation	M3GP 355MLB 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6322/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015381

#### Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed
D	T3	50 Hz	400 V	250.00 kW	750 r/min
Y	T3	50 Hz	690 V	250.00 kW	750 r/min
D	T3	50 Hz	415 V	250.00 kW	750 r/min

EX-Protection	Exec
Frame Size	355
Gas Group	IIC
Gross Weight	2210 kg
IC Class	IC411

IM Class	IMB3 IM1001
Insulation Class	ICLF
Invoice Description	M3GP 355MLB 8
IP Class	IP55
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Output Power	250 kW
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	2180 kg
Product Type	3GP2__M3GP_IE2_CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	T3
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

## Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE2 LV motors

Motors and Generators → Motors and Generators for Explosive Atmospheres → Increased Safety Ex ec Zone 2 Motors → Increased Safety IE2 Ex ec Motors

