

PRODUCT-DETAILS

3GGP401820-BDG

M3GP 400LKB 2



General Information

Product ID	3GGP401820-BDG
ABB Type Designation	M3GP 400LKB 2
Catalog Description	M3GP 400LKB 2

Additional Information

ABB Type Designation	M3GP 400LKB 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6317M/C3
Bearing NDE	6317M/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015394
Direction of Rotation	CW Clockwise
EX-Protection	Exec

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	690 V	630.00 kW	2987 r/min	611.00 A	0.890	96.50 %	2014.00 N·m	7.60
D	T3	50 Hz	400 V	630.00 kW	2987 r/min	1049.00 A	0.890	96.50 %	2014.00 N·m	7.60
D	T3	50 Hz	415 V	630.00 kW	2987 r/min	1024.00 A	0.880	96.50 %	2014.00 N·m	8.10

Gas Group	IIC
Gross Weight	3090 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE4 Full Load (100%) 96.5 % Partial Load (75%) 96.2 % Partial Load (50%) 95.6 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 400LKB 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	3050 kg
Product Type	3GP2__M3GP_IE2_CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	T3
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE2 LV motors

Motors and Generators → Motors and Generators for Explosive Atmospheres → Increased Safety Ex ec Zone 2 Motors → Increased Safety IE2 Ex ec Motors



