

PRODUCT-DETAILS

3GGP404820-ADG

M3GP 400LKB 8



General Information

Product ID	3GGP404820-ADG
ABB Type Designation	M3GP 400LKB 8
Catalog Description	M3GP 400LKB 8

Additional Information

ABB Type Designation	M3GP 400LKB 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6324/C3
Bearing NDE	6319/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015381
Direction of Rotation	CW Clockwise

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	690 V	355.00 kW	743 r/min	373.00 A	0.830	93.50 %	4562.00 N-m	6.80
D	T3	50 Hz	400 V	355.00 kW	743 r/min	641.00 A	0.830	93.50 %	4562.00 N-m	6.80
D	T3	50 Hz	415 V	355.00 kW	744 r/min	629.00 A	0.820	93.50 %	4559.00 N-m	8.10

EX-Protection	Exec
Frame Material	Cast Iron
Frame Size	400

Gas Group	IIC
Gross Weight	3240 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 93.5 % Partial Load (75%) 93.8 % Partial Load (50%) 93.3 %
IM Class	IMB3 IM1001
Insulation Class	ICLF
Invoice Description	M3GP 400LKB 8
IP Class	IP55
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	3200 kg
Product Type	3GP2_M3GP_IE2_CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	T3
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE2 LV motors

Motors and Generators → Motors and Generators for Explosive Atmospheres → Increased Safety Ex ec Zone 2 Motors → Increased Safety IE2 Ex ec Motors

