

PRODUCT-DETAILS

3GGP452530-BDG

M3GP 450LC 4



General Information

Product ID	3GGP452530-BDG
ABB Type Designation	M3GP 450LC 4
Catalog Description	M3GP 450LC 4

Additional Information

ABB Type Designation	M3GP 450LC 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6326/C3
Bearing NDE	6322/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015399
Direction of Rotation	CW Clockwise

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	690 V	1000.00 kW	1491 r/min	1000.00 A	0.860	95.10 %	6404.00 N-m	6.80
D	T3	50 Hz	400 V	1000.00 kW	1491 r/min	1724.00 A	0.860	95.10 %	6404.00 N-m	6.80
D	T3	50 Hz	415 V	1000.00 kW	1492 r/min	1677.00 A	0.850	95.10 %	6401.00 N-m	7.00

EX-Protection	Exec
Frame Material	Cast Iron
Frame Size	450

Gas Group	IIC
Gross Weight	4740 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 95.1 % Partial Load (75%) 94.9 % Partial Load (50%) 93.9 %
IM Class	IMB5 IM3001
Insulation Class	ICLF
Invoice Description	M3GP 450LC 4
IP Class	IP55
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	4700 kg
Product Type	3GP2_M3GP_IE2_CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	T3
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE2 LV motors

Motors and Generators → Motors and Generators for Explosive Atmospheres → Increased Safety Ex ec Zone 2 Motors → Increased Safety IE2 Ex ec Motors

