

PRODUCT-DETAILS

# 3GGP453520-ADG

## M3GP 450LB 6



### General Information

Product ID	3GGP453520-ADG
ABB Type Designation	M3GP 450LB 6
Catalog Description	M3GP 450LB 6

### Additional Information

ABB Type Designation	M3GP 450LB 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6326/C3
Bearing NDE	6322/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015394
Direction of Rotation	CW Clockwise

#### Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	690 V	710.00 kW	995 r/min	719.00 A	0.850	95.00 %	6814.00 N-m	7.00
D	T3	50 Hz	400 V	710.00 kW	995 r/min	1244.00 A	0.850	95.00 %	6814.00 N-m	7.00
D	T3	50 Hz	415 V	710.00 kW	995 r/min	1203.00 A	0.850	95.00 %	6812.00 N-m	7.80

Frame Material	Cast Iron
Frame Size	450
Gas Group	IIC
Gross Weight	4540 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 95.0 % Partial Load (75%) 95.0 % Partial Load (50%) 94.1 %
IM Class	IMB3 IM1001
Insulation Class	ICLF
Invoice Description	M3GP 450LB 6
IP Class	IP55
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	4500 kg
Product Type	3GP2_M3GP_IE2_CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	T3
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

---

## Categories

---

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE2 LV motors

Motors and Generators → Motors and Generators for Explosive Atmospheres → Increased Safety Ex ec Zone 2 Motors → Increased Safety IE2 Ex ec Motors



