


PRODUCT-DETAILS

3GJP081310-BDH

M3JP 80MA 2

For sale but "Obsolete", replaced by



General Information

Product ID	3GJP081310-BDH
ABB Type Designation	M3JP 80MA 2
Catalog Description	M3JP 80MA 2

Additional Information

ABB Type Designation	M3JP 80MA 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	0.75 kW	2876 r/min	0.92 A	0.850	80.10 %	2.40 N·m	7.30
D	T4	50 Hz	400 V	0.75 kW	2877 r/min	1.54 A	0.850	80.10 %	2.40 N·m	7.10
D	T4	50 Hz	415 V	0.75 kW	2886 r/min	1.50 A	0.850	80.30 %	2.40 N·m	7.50

EX-Protection	Exd
Frame Material	Cast Iron
Frame Size	80
Gas Group	IIB
Gross Weight	40 kg
IC Class	IC411

IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 80.1 % Partial Load (75%) 79.2 % Partial Load (50%) 75.3 %
IM Class	IMB5 IM3001
Insulation Class	ICLF
Invoice Description	M3JP 80MA 2
IP Class	IP55
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Package Level 1 Units	1 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	37 kg
Product Type	3JP2 _ M3JP _ IE2 _ Flameproof _ Exd _ motor
Quote Only	No
Replaced Product ID (OLD)	3GJP081310-BDG
Replacement Product ID (NEW)	3GJP081320-BDJ
Selling Unit of Measure	piece
Service Factor	1.00
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE2 High Efficiency LV Motors

