



PRODUCT-DETAILS

# 3GJP083310-ASH

## M3JP 80MA 6

### General Information

Product ID	3GJP083310-ASH
ABB Type Designation	M3JP 80MA 6
Catalog Description	M3JP 80MA 6

### Additional Information

ABB Type Designation	M3JP 80MA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015100
EX-Protection	Exd

#### Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	400 V	0.37 kW	952 r/min	1.37 A	0.580	71.60 %	3.70 N-m	4.30
D	T4	50 Hz	230 V	0.37 kW	954 r/min	2.36 A	0.600	68.40 %	3.70 N-m	4.50
Y	T4	50 Hz	415 V	0.37 kW	957 r/min	1.41 A	0.560	69.20 %	3.70 N-m	4.50

Gas Group	IIB
Gross Weight	41 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 68.4 % Partial Load (75%) 65.9 % Partial Load (50%) 59.4 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3JP 80MA 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	38 kg

Product Type	3JP2_M3JP_IE2_Flameproof_Ext_motor
Quote Only	No
Replaced Product ID (OLD)	3GJP083310-ASG
Replacement Product ID (NEW)	3GJP083310-ASJ
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)