

PRODUCT-DETAILS

# 3GJP092030-ASK

## Flameproof IE3 Premium Efficiency LV Motors, 1,1 kW, 400 V (3GJP092030-ASK)



### General Information

Product ID	3GJP092030-ASK
ABB Type Designation	M3JP 90SLC 4
Catalog Description	Flameproof IE3 Premium Efficiency LV Motors, 1,1 kW, 400 V (3GJP092030-ASK)

### Additional Information

ABB Type Designation	M3JP 90SLC 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Connection Configuration	Y
Country of Origin	Finland (FI) China (CN) Poland (PL)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

### Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	400 V	1.10 kW	1444 r/min	2.30 A	0.790	84.10 %	7.28 N·m	7.20
D	T4	50 Hz	230 V	1.10 kW	1444 r/min	4.00 A	0.790	84.10 %	7.28 N·m	7.20
Y	T4	50 Hz	380 V	1.10 kW	1435 r/min	2.40 A	0.800	84.10 %	7.28 N·m	6.50
D	T4	50 Hz	220 V	1.10 kW	1435 r/min	4.10 A	0.800	84.10 %	7.28 N·m	6.50
Y	T4	50 Hz	415 V	1.10 kW	1448 r/min	2.20 A	0.770	84.10 %	7.28 N·m	7.60
Y	T4	60 Hz	460 V	1.10 kW	1752 r/min	2.00 A	0.770	86.50 %	6.00 N·m	8.40

EX-Protection	Exdb
Frame Material	Cast Iron
Frame Size	90
Frequency (f)	50 Hz
Gas Group	IIB
Gross Weight	64 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 84.1 % Partial Load (75%) 84.2 % Partial Load (50%) 82.3 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 86.5 % Partial Load (75%) 85.9 % Partial Load (50%) 83.2 %
IM Class	IMB3 IM1001
Input Voltage (U <sub>in</sub> )	400 V
Insulation Class	ICLF
Invoice Description	M3JP 90SLC 4
IP Class	IP55
Made To Order	No
Medium Description	1.1kW, 4 Poles, Frame Size 90, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB3/IM1001 Mounting (3GJP092030-ASK)
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Output Power	1,1 kW
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Depth / Length	440 mm
Product Net Height	315 mm
Product Net Weight	61 kg
Product Net Width	201 mm
Product Type	3JP3_M3JP_IE3_Flameproof_Expd_motor
Quote Only	No
Replaced Product ID (OLD)	3GJP092010-ASL
SCIP	297e96db-dbee-43c1-ad2d-ddd583080bb8 Finland (FI)
Selling Unit of Measure	piece
Short Description	1.1kW, 4P, Frame Size 90, 3PH, 400V, 50Hz, IP55, IMB3/IM1001
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	T4
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

## Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors

