

PRODUCT-DETAILS

# 3GJP092030-BSL

## M3JP 90SLC 4

### General Information

Product ID	3GJP092030-BSL
ABB Type Designation	M3JP 90SLC 4
Catalog Description	M3JP 90SLC 4

### Additional Information

ABB Type Designation	M3JP 90SLC 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exd

#### Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	400 V	1.50 kW	1421 r/min	3.25 A	0.790	85.30 %	10.00 N·m	6.30
D	T4	50 Hz	230 V	1.50 kW	1421 r/min	5.64 A	0.790	85.30 %	10.00 N·m	6.30
Y	T4	50 Hz	415 V	1.50 kW	1427 r/min	3.35 A	0.740	85.30 %	10.00 N·m	6.30

Gas Group	IIB
Gross Weight	56 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 85.3 % Partial Load (75%) 85.3 % Partial Load (50%) 82.8 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3JP 90SLC 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4

Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	53 kg
Product Type	5JP3_M3JP_IE3_Flameproof_Ext_motor
Quote Only	No
Replacement Product ID (NEW)	3GJP092540-BSK
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	D-End top
Two Speed Motor	No
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)