



PRODUCT-DETAILS

3GJP093030-ASH

M3JP 90SLC 6

General Information

Product ID	3GJP093030-ASH
ABB Type Designation	M3JP 90SLC 6
Catalog Description	M3JP 90SLC 6

Additional Information

ABB Type Designation	M3JP 90SLC 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
EX-Protection	Exd

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Efficiency Factor	Torque	IS/IN
Y	T4	50 Hz	400 V	1.10 kW	933 r/min	2.97 A	0.700 78.50 %	11.30 N-m	5.00
D	T4	50 Hz	230 V	1.10 kW	933 r/min	5.15 A	0.700 78.50 %	11.30 N-m	5.00

Gas Group	IIB
Gross Weight	56 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 78.0 % Partial Load (75%) 74.0 % Partial Load (50%) 78.0 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3JP 90SLC 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	53 kg
Product Type	3JP2 M3JP IE2 Flameproof Exd motor

Quote Only	No
Replaced Product ID (OLD)	3GJP093030-ASG
Replacement Product ID (NEW)	3GJP093050-ASJ
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)