


PRODUCT-DETAILS

3GJP102510-ASL

M3JP 100LA 4



General Information

Product ID	3GJP102510-ASL
ABB Type Designation	M3JP 100LA 4
Catalog Description	M3JP 100LA 4

Additional Information

ABB Type Designation	M3JP 100LA 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6206-2Z/C3
Bearing NDE	6206-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exd

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	400 V	2.20 kW	1438 r/min	4.41 A	0.830	86.70 %	14.50 N·m	5.90
D	T4	50 Hz	230 V	2.20 kW	1438 r/min	7.67 A	0.830	86.70 %	14.50 N·m	5.90
Y	T4	50 Hz	415 V	2.20 kW	1443 r/min	4.34 A	0.810	86.70 %	14.50 N·m	6.30

Gas Group	IIB
Gross Weight	75 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 86.7 % Partial Load (75%) 87.8 % Partial Load (50%) 87.3 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3JP 100LA 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	70 kg
Product Type	5JP3_M3JP_IE3_Flameproof_Ext_motor
Quote Only	No
Replacement Product ID (NEW)	3GJP102810-ASK
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	D-End top
Two Speed Motor	No
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors



