

PRODUCT-DETAILS

3GJP131260-BSK

Flameproof IE3 Premium Efficiency LV Motors, 5,5 kW, 400 V (3GJP131260-BSK)



General Information

Product ID	3GJP131260-BSK
ABB Type Designation	M3JP 132SMF 2
Catalog Description	Flameproof IE3 Premium Efficiency LV Motors, 5,5 kW, 400 V (3GJP131260-BSK)

Additional Information

ABB Type Designation	M3JP 132SMF 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Connection Configuration	Y
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	400 V	5.50 kW	2902 r/min	9.70 A	0.900	90.70 %	18.20 N-m	7.30
D	T4	50 Hz	230 V	5.50 kW	2902 r/min	16.90 A	0.900	90.70 %	18.20 N-m	7.30
Y	T4	50 Hz	380 V	5.50 kW	2889 r/min	10.30 A	0.900	90.00 %	18.20 N-m	6.50
D	T4	50 Hz	220 V	5.50 kW	2889 r/min	17.80 A	0.900	90.00 %	18.20 N-m	6.50
Y	T4	50 Hz	415 V	5.50 kW	2909 r/min	9.30 A	0.900	90.80 %	18.20 N-m	7.80
Y	T4	60 Hz	460 V	5.50 kW	3512 r/min	8.40 A	0.900	90.10 %	15.00 N-m	8.30

EX-Protection	Exdb
Frame Material	Cast Iron
Frame Size	132
Frequency (f)	50 Hz
Gas Group	IIB
Gross Weight	129 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 90.0 % Partial Load (75%) 90.9 % Partial Load (50%) 90.8 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 90.1 % Partial Load (75%) 89.9 % Partial Load (50%) 88.2 %
IM Class	IMB5 IM3001
Input Voltage (U _{in})	400 V
Insulation Class	ICLF
IP Class	IP55
Made To Order	No
Medium Description	5.5kW, 2 Poles, Frame Size 132, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB5/IM3001 Mounting (3GJP131260-BSK)
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Output Power	5,5 kW
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Depth / Length	576 mm
Product Net Height	392 mm
Product Net Weight	124 kg
Product Net Width	250 mm
Product Type	3JP3__M3JP_IE3_Flameproof_Ext_motor
Quote Only	No
Replaced Product ID (OLD)	3GJP131230-BSL
SCIP	297e96db-dbee-43c1-ad2d-ddd583080bb8 Finland (FI)
Selling Unit of Measure	piece
Short Description	5.5kW, 2P, Frame Size 132, 3PH, 400V, 50Hz, IP55, IMB5/IM3001
Temperature Class Default	T4
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100

Voltage Code

S

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors

