



PRODUCT-DETAILS

3GJP132220-BSL

M3JP 132SMB 4

General Information

Product ID	3GJP132220-BSL
ABB Type Designation	M3JP 132SMB 4
Catalog Description	M3JP 132SMB 4

Additional Information

ABB Type Designation	M3JP 132SMB 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exd

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	400 V	5.50 kW	1458 r/min	11.80 A	0.750	89.60 %	36.00 N·m	7.80
D	T4	50 Hz	230 V	5.50 kW	1458 r/min	20.50 A	0.750	89.60 %	36.00 N·m	7.80
Y	T4	50 Hz	415 V	5.50 kW	1462 r/min	12.00 A	0.710	89.60 %	35.90 N·m	8.00

Gas Group	IIB
Gross Weight	116 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 89.6 % Partial Load (75%) 89.8 % Partial Load (50%) 88.5 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3JP 132SMB 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4

Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	111 kg
Product Type	5JP3_M3JP_IE3_Flameproof_Ext_motor
Quote Only	No
Replacement Product ID (NEW)	3GJP132260-BSK
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	D-End top
Two Speed Motor	No
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)