



PRODUCT-DETAILS

3GJP133240-BDH

M3JP 132SMD 6

General Information

Product ID	3GJP133240-BDH
ABB Type Designation	M3JP 132SMD 6
Catalog Description	M3JP 132SMD 6

Additional Information

ABB Type Designation	M3JP 132SMD 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
EX-Protection	Exd

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	5.50 kW	967 r/min	7.30 A	0.720	87.50 %	54.30 N-m	7.20
D	T4	50 Hz	400 V	5.50 kW	967 r/min	12.70 A	0.720	87.50 %	54.30 N-m	7.20

Gas Group	IIB
Gross Weight	114 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 87.4 % Partial Load (75%) 86.6 % Partial Load (50%) 83.7 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3JP 132SMD 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	109 kg
Product Type	3JP2 M3JP IE2 Flameproof Exd motor

Quote Only	No
Replaced Product ID (OLD)	3GJP133240-BDG
Replacement Product ID (NEW)	3GJP133260-BDJ
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)