

PRODUCT-DETAILS

# 3GJP133240-BSL

## (3GJP133240-BSL)

"No longer for sale" replaced by 3GJP133280-




---

### General Information

Product ID	3GJP133240-BSL
ABB Type Designation	M3JP 132SMD 6
Catalog Description	(3GJP133240-BSL)

---

### Additional Information

ABB Type Designation	M3JP 132SMD 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

#### Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	400 V	5.50 kW	969 r/min	12.70 A	0.700	88.00 %	54.20 N·m	7.10
D	T4	50 Hz	230 V	5.50 kW	969 r/min	22.10 A	0.700	88.00 %	54.20 N·m	7.10
Y	T4	50 Hz	415 V	5.50 kW	971 r/min	11.70 A	0.730	88.00 %	54.20 N·m	7.30

EX-Protection	Exd
Frame Material	Cast Iron
Frame Size	132
Gas Group	IIB
Gross Weight	114 kg

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 88.0 % Partial Load (75%) 87.8 % Partial Load (50%) 85.5 %
IM Class	IMB5 IM3001
Insulation Class	ICLF
Invoice Description	M3JP 132SMD 6
IP Class	IP55
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	109 kg
Product Type	5JP3__M3JP_IE3_Flameproof_Ext_motor
Quote Only	No
Replacement Product ID (NEW)	3GJP133280-BSK
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

## Categories

---

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors

