



PRODUCT-DETAILS

3GJP134240-ADH

M3JP 132SMD 8

General Information

Product ID	3GJP134240-ADH
ABB Type Designation	M3JP 132SMD 8
Catalog Description	M3JP 132SMD 8

Additional Information

ABB Type Designation	M3JP 132SMD 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
EX-Protection	Exd

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	3.00 kW	711 r/min	4.62 A	0.710	79.90 %	40.40 N-m	4.10
D	T4	50 Hz	400 V	3.00 kW	711 r/min	7.98 A	0.710	79.90 %	40.40 N-m	4.10

Gas Group	IIB
Gross Weight	114 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE1 Full Load (100%) 79.3 % Partial Load (75%) 79.3 % Partial Load (50%) 76.5 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3JP 132SMD 8
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	109 kg
Product Type	3JP2 M3JP IE2 Flameproof Exd motor

Quote Only	No
Replaced Product ID (OLD)	3GJP134240-ADG
Replacement Product ID (NEW)	3GJP134220-ADJ
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)