



PRODUCT-DETAILS

# 3GJP163410-BDL

## M3JP 160MLA 6

### General Information

Product ID	3GJP163410-BDL
ABB Type Designation	M3JP 160MLA 6
Catalog Description	M3JP 160MLA 6

### Additional Information

ABB Type Designation	M3JP 160MLA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6309/C3
Bearing NDE	6309/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
EX-Protection	Exd

#### Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Efficiency Factor	Torque	IS/IN
Y	T4	50 Hz	690 V	7.50 kW	975 r/min	9.10 A	0.770	89.10 % 73.24 N·m	5.70
D	T4	50 Hz	400 V	7.50 kW	975 r/min	15.70 A	0.770	89.10 % 73.24 N·m	5.70
D	T4	50 Hz	415 V	7.50 kW	976 r/min	15.40 A	0.760	89.10 % 73.10 N·m	6.10
D	T4	60 Hz	440 V	7.50 kW	1176 r/min	14.00 A	0.780	91.00 % 60.80 N·m	6.10
D	T4	60 Hz	460 V	7.50 kW	1179 r/min	13.50 A	0.770	91.00 % 60.70 N·m	6.70

Gas Group	IIB
Gross Weight	235 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 89.1 % Partial Load (75%) 89.7 % Partial Load (50%) 89.4 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 91.0 % Partial Load (75%) 91.1 % Partial Load (50%) 89.9 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3JP 160MLA 6

Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	225 kg
Product Type	5JP3__M3JP_IE3_Flameproof_Ext_motor
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC_60034-1
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)