


PRODUCT-DETAILS

3GJP164430-ADH

M3JP 160MLC 8



General Information

Product ID	3GJP164430-ADH
ABB Type Designation	M3JP 160MLC 8
Catalog Description	M3JP 160MLC 8

Additional Information

ABB Type Designation	M3JP 160MLC 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6309/C3
Bearing NDE	6309/C3
Country of Origin	Finland (FI) China (CN)
Customs Tariff Number	85015220

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	7.50 kW	718 r/min	11.00 A	0.700	82.00 %	99.80 N·m	11.10
D	T4	50 Hz	400 V	7.50 kW	718 r/min	19.30 A	0.700	82.00 %	99.80 N·m	5.70
D	T4	50 Hz	415 V	7.50 kW	721 r/min	19.00 A	0.670	82.30 %	99.40 N·m	6.00

EX-Protection	Exdb
Frame Material	Cast Iron
Frame Size	160
Gas Group	IIB
Gross Weight	261 kg

IC Class	IC411
IE Class Data (50 Hz)	IE Class NA Full Load (100%) 82.0 % Partial Load (75%) 84.0 % Partial Load (50%) 84.0 %
IM Class	IMB3 IM1001
Insulation Class	ICLF
Invoice Description	M3JP 160MLC 8
IP Class	IP55
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	251 kg
Product Type	3JP2__M3JP_IE2_Flameproof_Exd_motor
Quote Only	No
Replaced Product ID (OLD)	3GJP164430-ADG
SCIP	297e96db-dbee-43c1-ad2d-ddd583080bb8 Finland (FI)
Selling Unit of Measure	piece
Service Factor	1.00
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE2 High Efficiency LV Motors

