

---

PRODUCT-DETAILS

# 3GJP201410-BDL

## M3JP 200MLA 2



---

### General Information

Product ID	3GJP201410-BDL
ABB Type Designation	M3JP 200MLA 2
Catalog Description	M3JP 200MLA 2

---

### Additional Information

ABB Type Designation	M3JP 200MLA 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6312/C3
Bearing NDE	6310/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
EX-Protection	Exd
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	30.00 kW	2957 r/min	30.50 A	0.880	93.30 %	96.92 N·m	7.50
D	T4	50 Hz	400 V	30.00 kW	2957 r/min	52.40 A	0.880	93.30 %	96.92 N·m	7.50
D	T4	50 Hz	415 V	30.00 kW	2961 r/min	51.10 A	0.870	93.30 %	96.80 N·m	8.10
D	T4	60 Hz	440 V	30.00 kW	3559 r/min	47.20 A	0.890	92.40 %	80.52 N·m	7.90
D	T4	60 Hz	460 V	30.00 kW	3563 r/min	45.70 A	0.880	92.40 %	80.43 N·m	8.70

Gas Group	IIB
Gross Weight	342 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 93.3 % Partial Load (75%) 93.6 % Partial Load (50%) 93.3 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 92.4 % Partial Load (75%) 92.4 % Partial Load (50%) 91.2 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3JP 200MLA 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	332 kg
Product Type	5JP3_M3JP_IE3_Flameproof_Exd_motor
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC_60034-1
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

## Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors

