

PRODUCT-DETAILS

3GJP223210-ADL**M3JP 225SMA 6****General Information**

Product ID	3GJP223210-ADL
ABB Type Designation	M3JP 225SMA 6
Catalog Description	M3JP 225SMA 6

Additional Information

ABB Type Designation	M3JP 225SMA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6313/C3
Bearing NDE	6312/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
EX-Protection	Exd
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	30.00 kW	988 r/min	34.90 A	0.770	92.90 %	290.60 N·m	7.70
D	T4	50 Hz	400 V	30.00 kW	988 r/min	60.40 A	0.770	92.90 %	290.60 N·m	7.70
D	T4	50 Hz	415 V	30.00 kW	989 r/min	61.80 A	0.730	92.90 %	290.60 N·m	8.00
D	T4	60 Hz	440 V	30.00 kW	1189 r/min	53.50 A	0.790	93.40 %	241.40 N·m	8.10
D	T4	60 Hz	460 V	30.00 kW	1190 r/min	52.60 A	0.770	93.50 %	241.40 N·m	8.70

Gas Group	IIB
Gross Weight	429 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 92.9 % Partial Load (75%) 92.6 % Partial Load (50%) 91.0 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 93.4 % Partial Load (75%) 93.5 % Partial Load (50%) 92.6 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3JP 225SMA 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	419 kg
Product Type	5JP3__M3JP_IE3_Flameproof_Ext_motor
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC_60034-1
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors

