

PRODUCT-DETAILS

3GJP253210-BDG

M3JP 250SMA 6



General Information

Product ID	3GJP253210-BDG
ABB Type Designation	M3JP 250SMA 6
Catalog Description	M3JP 250SMA 6

Additional Information

ABB Type Designation	M3JP 250SMA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6315/C3
Bearing NDE	6313/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
EX-Protection	Exd

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	37.00 kW	990 r/min	41.00 A	0.810	92.20 %	357.00 N·m	6.50
D	T4	50 Hz	400 V	37.00 kW	990 r/min	70.60 A	0.810	92.20 %	357.00 N·m	6.50
D	T4	50 Hz	415 V	37.00 kW	991 r/min	68.90 A	0.810	92.20 %	357.00 N·m	6.70

Gross Weight	465 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 92.2 % Partial Load (75%) 92.5 % Partial Load (50%) 91.8 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3JP 250SMA 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	455 kg
Product Type	3JP2_ M3JP_ IE2_ Flameproof_ Exd_ motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE2 High Efficiency LV Motors

