

PRODUCT-DETAILS

3GJP311210-ADG

M3JP 315SMA 2



General Information

Product ID	3GJP311210-ADG
ABB Type Designation	M3JP 315SMA 2
Catalog Description	M3JP 315SMA 2

Additional Information

ABB Type Designation	M3JP 315SMA 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6316/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015381
Direction of Rotation	Both sides
EX-Protection	Exd

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	110.00 kW	2982 r/min	112.00 A	0.860	94.90 %	352.00 N·m	7.40
D	T4	50 Hz	400 V	110.00 kW	2982 r/min	197.00 A	0.860	94.90 %	352.00 N·m	7.40
D	T4	50 Hz	415 V	110.00 kW	2983 r/min	192.00 A	0.850	94.90 %	352.00 N·m	8.10

Gas Group	IIB
Gross Weight	1000 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 94.9 % Partial Load (75%) 94.3 % Partial Load (50%) 92.8 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3JP 315SMA 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	980 kg
Product Type	3JP2_ M3JP_ IE2_ Flameproof_ Exd_ motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE2 High Efficiency LV Motors

