


PRODUCT-DETAILS

3GJP311230-BDG

M3JP 315SMC 2



General Information

Product ID	3GJP311230-BDG
ABB Type Designation	M3JP 315SMC 2
Catalog Description	M3JP 315SMC 2

Additional Information

ABB Type Designation	M3JP 315SMC 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6316/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015381
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	160.00 kW	2981 r/min	157.00 A	0.890	95.40 %	512.00 N-m	7.50
D	T4	50 Hz	400 V	160.00 kW	2981 r/min	271.00 A	0.890	95.40 %	512.00 N-m	7.50
D	T4	50 Hz	415 V	160.00 kW	2982 r/min	261.00 A	0.890	95.50 %	512.00 N-m	8.10

EX-Protection	Exdb
Frame Material	Cast Iron
Frame Size	315

Gas Group	IIB
Gross Weight	1045 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 95.4 % Partial Load (75%) 95.2 % Partial Load (50%) 94.2 %
IM Class	IMB5 IM3001
Insulation Class	ICLF
Invoice Description	M3JP 315SMC 2
IP Class	IP55
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	1025 kg
Product Type	3JP2_M3JP_IE2_Flameproof_Exd_motor
Quote Only	No
SCIP	297e96db-dbee-43c1-ad2d-ddd583080bb8 Finland (FI)
Selling Unit of Measure	piece
Service Factor	1.00
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE2 High Efficiency LV Motors

