

## PRODUCT-DETAILS

**3GJP313810-ADK****M3JP 315LKA 6****General Information**

Product ID	3GJP313810-ADK
ABB Type Designation	M3JP 315LKA 6
Catalog Description	M3JP 315LKA 6

**Additional Information**

ABB Type Designation	M3JP 315LKA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6319/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI) China (CN)
Customs Tariff Number	85015381
Direction of Rotation	Both sides
EX-Protection	Exd
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	132.00 kW	993 r/min	141.00 A	0.820	95.90 %	1269.00 N·m	6.90
D	T4	50 Hz	400 V	132.00 kW	993 r/min	243.00 A	0.820	95.90 %	1269.00 N·m	6.90
Y	T4	50 Hz	660 V	132.00 kW	992 r/min	146.00 A	0.830	95.90 %	1270.00 N·m	6.20
D	T4	50 Hz	380 V	132.00 kW	992 r/min	254.00 A	0.830	95.90 %	1270.00 N·m	6.20
D	T4	50 Hz	415 V	132.00 kW	994 r/min	238.00 A	0.810	95.90 %	1268.00 N·m	7.30
D	T4	60 Hz	460 V	132.00 kW	1194 r/min	215.00 A	0.810	96.10 %	1055.00 N·m	7.90

Gas Group	IIB
Gross Weight	1510 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 95.9 % Partial Load (75%) 96.0 % Partial Load (50%) 95.7 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 96.1 % Partial Load (75%) 96.0 % Partial Load (50%) 95.5 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3JP 315LKA 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	1490 kg
Product Type	3JP3__M3JP_IE3_Flameproof_Ext_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

## Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors

