


PRODUCT-DETAILS

3GJP353220-BDK

M3JP 355SMB 6



General Information

Product ID	3GJP353220-BDK
ABB Type Designation	M3JP 355SMB 6
Catalog Description	M3JP 355SMB 6

Additional Information

ABB Type Designation	M3JP 355SMB 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6322/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI) China (CN)
Customs Tariff Number	85015381
Direction of Rotation	Both sides
EX-Protection	Exd
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	160.00 kW	995 r/min	171.00 A	0.820	96.10 %	1536.00 N·m	7.00
D	T4	50 Hz	400 V	160.00 kW	995 r/min	294.00 A	0.820	96.10 %	1536.00 N·m	7.00
Y	T4	50 Hz	660 V	160.00 kW	994 r/min	177.00 A	0.830	96.10 %	1537.00 N·m	6.30
D	T4	50 Hz	380 V	160.00 kW	994 r/min	308.00 A	0.830	96.10 %	1537.00 N·m	6.30
D	T4	50 Hz	415 V	160.00 kW	995 r/min	288.00 A	0.810	96.10 %	1535.00 N·m	7.50
D	T4	60 Hz	460 V	160.00 kW	1195 r/min	260.00 A	0.810	96.10 %	1278.00 N·m	7.90

Gas Group	IIB
Gross Weight	1808 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 96.1 % Partial Load (75%) 96.1 % Partial Load (50%) 95.6 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 96.1 % Partial Load (75%) 96.0 % Partial Load (50%) 95.3 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3JP 355SMB 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	1778 kg
Product Type	3JP3__M3JP_IE3_Flameproof_Exd_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors

