

PRODUCT-DETAILS

3GJP403820-BDK

No Description Available



General Information

Product ID	3GJP403820-BDK
ABB Type Designation	M3JP 400LKB 6
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3JP 400LKB 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6324/C3
Bearing NDE	6319/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015394
EX-Protection	Exdb
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	450.00 kW	994 r/min	475.00 A	0.820	95.80 %	4323.00 N-m	7.40
D	T4	50 Hz	400 V	450.00 kW	994 r/min	819.00 A	0.820	95.80 %	4323.00 N-m	7.40
D	T4	50 Hz	415 V	450.00 kW	994 r/min	804.00 A	0.810	95.80 %	4321.00 N-m	7.40
D	T4	60 Hz	460 V	450.00 kW	1194 r/min	713.00 A	0.820	95.80 %	3598.00 N-m	7.90

Gas Group	IIB
Gross Weight	3470 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 95.8 % Partial Load (75%) 95.8 % Partial Load (50%) 95.0 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 95.8 % Partial Load (75%) 95.6 % Partial Load (50%) 94.7 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	3430 kg
Product Type	3JP3__M3JP_IE3_Flameproof_Ext_motor
Quote Only	No
SCIP	297e96db-dbee-43c1-ad2d-ddd583080bb8 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors

