
PRODUCT-DETAILS

3GKP083310-CSK

No Description Available



General Information

Product ID	3GKP083310-CSK
ABB Type Designation	M3KP 80MA 6
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3KP 80MA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
EX-Protection	Exdbeb
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	400 V	0.25 kW	937 r/min	0.76 A	0.640	73.30 %	2.52 N-m	2.60
D	T4	50 Hz	230 V	0.25 kW	937 r/min	1.33 A	0.640	73.30 %	2.52 N-m	2.60
Y	T4	50 Hz	380 V	0.25 kW	929 r/min	0.75 A	0.680	73.60 %	2.52 N-m	2.50
D	T4	50 Hz	220 V	0.25 kW	929 r/min	1.31 A	0.680	73.60 %	2.52 N-m	2.50
Y	T4	50 Hz	415 V	0.25 kW	941 r/min	0.79 A	0.600	72.60 %	2.52 N-m	2.60
Y	T4	60 Hz	460 V	0.25 kW	1143 r/min	0.68 A	0.600	75.40 %	2.06 N-m	3.10

Gas Group	IIB
Gross Weight	38 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 72.6 % Partial Load (75%) 70.7 % Partial Load (50%) 65.0 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 75.4 % Partial Load (75%) 73.5 % Partial Load (50%) 68.1 %
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor	3GKP083310-BSK
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	35 kg
Product Type	3KP3_M3KP_IE3_Flameproof_Exde_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class	T4
Default	
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors

