
PRODUCT-DETAILS

3GKP091020-CDK

No Description Available



General Information

| | |
|----------------------|--------------------------|
| Product ID | 3GKP091020-CDK |
| ABB Type Designation | M3KP 90SLB 2 |
| Catalog Description | No Description Available |

Additional Information

| | |
|-----------------------|--------------|
| ABB Type Designation | M3KP 90SLB 2 |
| Altitude | 1000 m |
| Ambient Temperature | 40 °C |
| Bearing | 6205-2Z/C3 |
| Bearing NDE | 6204-2Z/C3 |
| Country of Origin | Finland (FI) |
| Customs Tariff Number | 85015220 |
| Direction of Rotation | Both sides |
| EX-Protection | Exdbeb |
| Electrical Data | |

| Conn | Temp Class | Freq | Voltage | Power | Speed | Current | Power Factor | Efficiency | Torque | IS/IN |
|------|------------|-------|---------|---------|------------|---------|--------------|------------|----------|-------|
| Y | T4 | 50 Hz | 690 V | 1.50 kW | 2892 r/min | 1.61 A | 0.890 | 86.40 % | 4.80 N·m | 7.30 |
| D | T4 | 50 Hz | 400 V | 1.50 kW | 2892 r/min | 2.70 A | 0.890 | 86.40 % | 4.80 N·m | 7.30 |
| Y | T4 | 50 Hz | 660 V | 1.50 kW | 2878 r/min | 1.70 A | 0.890 | 86.40 % | 4.80 N·m | 6.40 |
| D | T4 | 50 Hz | 380 V | 1.50 kW | 2878 r/min | 2.90 A | 0.890 | 86.40 % | 4.80 N·m | 6.40 |
| D | T4 | 50 Hz | 415 V | 1.50 kW | 2900 r/min | 2.70 A | 0.880 | 86.40 % | 4.80 N·m | 7.90 |
| D | T4 | 60 Hz | 460 V | 1.50 kW | 3506 r/min | 2.40 A | 0.890 | 86.40 % | 4.00 N·m | 8.50 |

| | |
|-------------------------------|---|
| Gas Group | IIB |
| Gross Weight | 53 kg |
| IC Class | IC411 |
| IE Class Data (50 Hz) | IE Class IE3 Full Load (100%) 86.4 % Partial Load (75%) 87.1 % Partial Load (50%) 86.1 % |
| IE Class Data (60 Hz) | IE Class IE3 Full Load (100%) 86.4 % Partial Load (75%) 86.1 % Partial Load (50%) 83.7 % |
| IM Class | IMB14 IM3601 |
| IP Class | IP55 |
| Insulation Class | ICLF |
| Made To Order | No |
| Minimum Order Quantity | 1 piece |
| Number of Poles (High) | 2 |
| Order Multiple | 1 piece |
| Package Level 1 Units | 0 carton |
| Pre Modified Motor Product ID | 3GKP091020-BDK |
| Product Name | 3-Phase squirrel cage motor |
| Product Net Weight | 50 kg |
| Product Type | 3KP3_M3KP_IE3_Flameproof_Exde_motor |
| Quote Only | No |
| Replaced Product ID (OLD) | 3GKP091010-CDL |
| Selling Unit of Measure | piece |
| Temperature Class Default | T4 |
| Terminator Box Location | D-End top |
| Two Speed Motor | No |
| Type of Duty | S1 |
| UNSPSC | 26101100 |
| Voltage Code | D |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors

