

PRODUCT-DETAILS

# 3GKP094010-ASH

## M3KP 90SLA 8



### General Information

Product ID	3GKP094010-ASH
ABB Type Designation	M3KP 90SLA 8
Catalog Description	M3KP 90SLA 8

### Additional Information

ABB Type Designation	M3KP 90SLA 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015100
EX-Protection	Exde

#### Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	400 V	0.37 kW	697 r/min	1.33 A	0.630	65.50 %	5.10 N·m	3.00
D	T4	50 Hz	230 V	0.37 kW	697 r/min	2.32 A	0.630	65.50 %	5.10 N·m	3.00
Y	T4	50 Hz	415 V	0.37 kW	702 r/min	1.33 A	0.630	65.50 %	5.00 N·m	3.10

Gas Group	IIB
Gross Weight	44 kg
IC Class	IC411

## IE Class Data (50 Hz)

IE Class IE2  
 Full Load (100%) 65.5 %  
 Partial Load (75%) 63.7 %  
 Partial Load (50%) 57.6 %

IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3KP 90SLA 8
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	41 kg
Product Type	3KP2__M3KP_IE2_Flameproof_Exde_motor
Quote Only	No
Replaced Product ID (OLD)	3GKP094010-ASG
Replacement Product ID (NEW)	3GKP094020-ASJ
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

## Categories

---

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE2 High Efficiency LV Motors

