

PRODUCT-DETAILS

3GKP112370-ASK

Flameproof IE3 Premium Efficiency LV Motors, 4 kW, 400 V (3GKP112370-ASK)



General Information

Product ID	3GKP112370-ASK
ABB Type Designation	M3KP 112MG 4
Catalog Description	Flameproof IE3 Premium Efficiency LV Motors, 4 kW, 400 V (3GKP112370-ASK)

Additional Information

ABB Type Designation	M3KP 112MG 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6206-2Z/C3
Bearing NDE	6206-2Z/C3
Connection Configuration	Y
Country of Origin	Finland (FI) Poland (PL)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	400 V	4.00 kW	1454 r/min	8.70 A	0.750	88.70 %	26.30 N-m	7.50
D	T4	50 Hz	230 V	4.00 kW	1454 r/min	15.10 A	0.750	88.70 %	26.30 N-m	7.50
Y	T4	50 Hz	380 V	4.00 kW	1447 r/min	8.90 A	0.770	88.60 %	26.40 N-m	6.80
D	T4	50 Hz	220 V	4.00 kW	1447 r/min	15.40 A	0.770	88.60 %	26.40 N-m	6.80
Y	T4	50 Hz	415 V	4.00 kW	1458 r/min	8.60 A	0.730	88.90 %	26.20 N-m	7.90
Y	T4	60 Hz	460 V	4.00 kW	1760 r/min	7.60 A	0.740	89.80 %	21.70 N-m	8.80

EX-Protection	Exdbeb
Frame Material	Cast Iron
Frame Size	112
Frequency (f)	50 Hz
Gas Group	IIB
Gross Weight	76 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 88.6 % Partial Load (75%) 89.5 % Partial Load (50%) 89.4 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 89.8 % Partial Load (75%) 89.7 % Partial Load (50%) 88.3 %
IM Class	IMB3 IM1001
Input Voltage (U _{in})	400 V
Insulation Class	ICLF
Invoice Description	M3KP 112MG 4
IP Class	IP55
Made To Order	No
Medium Description	4kW, 4 Poles, Frame Size 112, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB3/IM1001 Mounting (3GKP112370-ASK)
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Output Power	4 kW
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Depth / Length	485 mm
Product Net Height	309 mm
Product Net Weight	71 kg
Product Net Width	230 mm
Product Type	3KP3_M3KP_IE3_Flameproof_Exde_motor
Quote Only	No
Replaced Product ID (OLD)	3GKP112330-ASL
Selling Unit of Measure	piece
Short Description	4kW, 4P, Frame Size 112, 3PH, 400V, 50Hz, IP55, IMB3/IM1001
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	T4
Terminator Box Location	D-End top
Two Speed Motor	No

Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors

