

PRODUCT-DETAILS

3GKP114330-BDK

Flameproof IE3 Premium Efficiency LV Motors, 1,5 kW, 400 V (3GKP114330-BDK)



General Information

Product ID	3GKP114330-BDK
ABB Type Designation	M3KP 112MC 8
Catalog Description	Flameproof IE3 Premium Efficiency LV Motors, 1,5 kW, 400 V (3GKP114330-BDK)

Additional Information

ABB Type Designation	M3KP 112MC 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6206-2Z/C3
Bearing NDE	6206-2Z/C3
Connection Configuration	D
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	1.50 kW	717 r/min	2.39 A	0.620	79.70 %	19.90 N-m	4.30
D	T4	50 Hz	400 V	1.50 kW	717 r/min	4.12 A	0.620	79.70 %	19.90 N-m	4.30
Y	T4	50 Hz	660 V	1.50 kW	712 r/min	2.40 A	0.650	79.70 %	20.10 N-m	4.00
D	T4	50 Hz	380 V	1.50 kW	712 r/min	4.17 A	0.650	79.70 %	20.10 N-m	4.00
D	T4	50 Hz	415 V	1.50 kW	723 r/min	4.08 A	0.600	79.70 %	19.80 N-m	4.50
D	T4	60 Hz	460 V	1.50 kW	872 r/min	3.70 A	0.580	84.00 %	16.40 N-m	4.70

EX-Protection	Exdbeb
Frame Material	Cast Iron
Frame Size	112
Frequency (f)	50 Hz
Gas Group	IIB
Gross Weight	77 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 79.7 % Partial Load (75%) 79.5 % Partial Load (50%) 77.6 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 84.0 % Partial Load (75%) 83.6 % Partial Load (50%) 81.3 %
IM Class	IMB5 IM3001
Input Voltage (U _{in})	400 V
Insulation Class	ICLF
IP Class	IP55
Made To Order	No
Medium Description	1.5kW, 8 Poles, Frame Size 112, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB5/IM3001 Mounting (3GKP114330-BDK)
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Output Power	1,5 kW
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Depth / Length	485 mm
Product Net Height	309 mm
Product Net Weight	72 kg
Product Net Width	230 mm
Product Type	3KP3_M3KP_IE3_Flameproof_Exde_motor
Quote Only	No
Selling Unit of Measure	piece
Short Description	1.5kW, 8P, Frame Size 112, 3PH, 400V, 50Hz, IP55, IMB5/IM3001
Temperature Class Default	T4
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors

