



PRODUCT-DETAILS

3GKP131240-ASH

M3KP 132SMD 2

General Information

Product ID	3GKP131240-ASH
ABB Type Designation	M3KP 132SMD 2
Catalog Description	M3KP 132SMD 2

Additional Information

ABB Type Designation	M3KP 132SMD 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
EX-Protection	Exde

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	400 V	7.50 kW	2914 r/min	13.40 A	0.900	89.20 %	24.60 N·m	7.20
D	T4	50 Hz	230 V	7.50 kW	2914 r/min	23.40 A	0.900	89.20 %	24.60 N·m	7.10
Y	T4	50 Hz	415 V	7.50 kW	2920 r/min	13.00 A	0.890	89.40 %	24.55 N·m	7.70

Gas Group	IIB
Gross Weight	105 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 88.0 % Partial Load (75%) 87.0 % Partial Load (50%) 88.0 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3KP 132SMD 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor

Product Net Weight	100 kg
Product Type	3KP2__M3KP_IE2_Flameproof_Exde_motor
Quote Only	No
Replaced Product ID (OLD)	3GKP131240-ASG
Replacement Product ID (NEW)	3GKP131230-ASJ
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)