



PRODUCT-DETAILS

# 3GKP133230-ASH

## M3KP 132SMC 6

### General Information

Product ID	3GKP133230-ASH
ABB Type Designation	M3KP 132SMC 6
Catalog Description	M3KP 132SMC 6

### Additional Information

ABB Type Designation	M3KP 132SMC 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
EX-Protection	Exde

#### Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Efficiency Factor	Torque	IS/IN
Y	T4	50 Hz	400 V	4.00 kW	967 r/min	9.26 A	0.750 85.70 %	39.50 N·m	6.40
D	T4	50 Hz	230 V	4.00 kW	967 r/min	16.10 A	0.750 85.70 %	39.50 N·m	6.30
Y	T4	50 Hz	415 V	4.00 kW	970 r/min	9.30 A	0.730 85.70 %	39.40 N·m	6.60

Gas Group	IIB
Gross Weight	103 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 84.0 % Partial Load (75%) 81.0 % Partial Load (50%) 84.0 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3KP 132SMC 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	98 kg
Product Type	3KP2__M3KP_IE2_Flameproof_Exde_motor

Quote Only	No
Replaced Product ID (OLD)	3GKP133230-ASG
Replacement Product ID (NEW)	3GKP133230-ASJ
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)