

PRODUCT-DETAILS

# 3GKP133280-ASK

## Flameproof IE3 Premium Efficiency LV Motors, 5,5 kW, 400 V (3GKP133280-ASK)



### General Information

Product ID	3GKP133280-ASK
ABB Type Designation	M3KP 132SMH 6
Catalog Description	Flameproof IE3 Premium Efficiency LV Motors, 5.5 kW, 400 V (3GKP133280-ASK)

### Additional Information

ABB Type Designation	M3KP 132SMH 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Connection Configuration	Y
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

### Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	400 V	5.50 kW	966 r/min	12.10 A	0.730	88.00 %	54.10 N·m	5.00
D	T4	50 Hz	230 V	5.50 kW	966 r/min	21.10 A	0.730	88.00 %	54.10 N·m	5.00
Y	T4	50 Hz	380 V	5.50 kW	962 r/min	12.50 A	0.750	88.00 %	54.10 N·m	4.60
D	T4	50 Hz	220 V	5.50 kW	962 r/min	21.60 A	0.750	88.00 %	54.10 N·m	4.60
Y	T4	50 Hz	415 V	5.50 kW	968 r/min	13.50 A	0.630	88.00 %	54.10 N·m	5.20
Y	T4	60 Hz	460 V	5.50 kW	1169 r/min	10.60 A	0.720	91.00 %	44.70 N·m	5.70

Frame Material	Cast Iron
Frame Size	132
Frequency (f)	50 Hz
Gas Group	IIB
Gross Weight	114 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 88.0 % Partial Load (75%) 88.6 % Partial Load (50%) 88.0 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 91.0 % Partial Load (75%) 91.2 % Partial Load (50%) 90.3 %
IM Class	IMB3 IM1001
Input Voltage (U <sub>in</sub> )	400 V
Insulation Class	ICLF
Invoice Description	M3KP 132SMH 6
IP Class	IP55
Made To Order	No
Medium Description	5.5kW, 6 Poles, Frame Size 132, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB3/IM1001 Mounting (3GKP133280-ASK)
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Output Power	5,5 kW
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Depth / Length	576 mm
Product Net Height	346 mm
Product Net Weight	109 kg
Product Net Width	294 mm
Product Type	3KP3_M3KP_IE3_Flameproof_Exde_motor
Quote Only	No
Replaced Product ID (OLD)	3GKP133240-ASL
Selling Unit of Measure	piece
Short Description	5.5kW, 6P, Frame Size 132, 3PH, 400V, 50Hz, IP55, IMB3/IM1001
Temperature Class Default	T4
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

## Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors

