



PRODUCT-DETAILS

# 3GKP161430-ADH

## M3KP 160MLC 2

### General Information

Product ID	3GKP161430-ADH
ABB Type Designation	M3KP 160MLC 2
Catalog Description	M3KP 160MLC 2

### Additional Information

ABB Type Designation	M3KP 160MLC 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6309/C3
Bearing NDE	6309/C3
Country of Origin	Finland (FI) Poland (PL)
Customs Tariff Number	85015230
EX-Protection	Exde

#### Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	18.50 kW	2934 r/min	18.70 A	0.900	91.60 %	60.30 N·m	7.40
D	T4	50 Hz	400 V	18.50 kW	2934 r/min	32.40 A	0.900	91.60 %	60.30 N·m	7.40
D	T4	50 Hz	415 V	18.50 kW	2939 r/min	31.90 A	0.890	91.70 %	60.15 N·m	7.90

Gas Group	IIB
Gross Weight	237 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 91.6 % Partial Load (75%) 92.4 % Partial Load (50%) 92.3 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3KP 160MLC 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Package Level 1 Units	1 pallet (lift)

Product Name	3-Phase squirrel cage motor
Product Net Weight	227 kg
Product Type	3KP2__M3KP_IE2_Flameproof_Exde_motor
Quote Only	No
Replaced Product ID (OLD)	3GKP161430-ADG
Selling Unit of Measure	piece
Stocked At (Warehouses)	Central Stock Europe
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)