
PRODUCT-DETAILS

3GKP202410-ADK

Flameproof IE3 Premium Efficiency LV Motors, 30 kW, 400 V (3GKP202410-ADK)



General Information

Product ID	3GKP202410-ADK
ABB Type Designation	M3KP 200MLA 4
Catalog Description	Flameproof IE3 Premium Efficiency LV Motors, 30 kW, 400 V (3GKP202410-ADK)

Additional Information

ABB Type Designation	M3KP 200MLA 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6312/C3
Bearing NDE	6310/C3
Connection Configuration	D
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	30.00 kW	1484 r/min	31.60 A	0.840	93.60 %	193.00 N-m	8.30
D	T4	50 Hz	400 V	30.00 kW	1484 r/min	54.60 A	0.840	93.60 %	193.00 N-m	8.30
Y	T4	50 Hz	660 V	30.00 kW	1481 r/min	32.80 A	0.850	94.10 %	193.00 N-m	7.50
D	T4	50 Hz	380 V	30.00 kW	1481 r/min	56.90 A	0.850	94.10 %	193.00 N-m	7.50
D	T4	50 Hz	415 V	30.00 kW	1485 r/min	53.80 A	0.820	93.60 %	193.00 N-m	8.80
D	T4	60 Hz	460 V	30.00 kW	1786 r/min	47.90 A	0.830	94.70 %	160.00 N-m	9.40

EX-Protection	Exdbeb
Frame Material	Cast Iron
Frame Size	200
Frequency (f)	50 Hz
Gas Group	IIB
Gross Weight	357 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 93.6 % Partial Load (75%) 93.7 % Partial Load (50%) 93.0 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 94.7 % Partial Load (75%) 94.8 % Partial Load (50%) 94.1 %
IM Class	IMB3 IM1001
Input Voltage (U _{in})	400 V
Insulation Class	ICLF
Invoice Description	M3KP 200MLA 4
IP Class	IP55
Made To Order	No
Medium Description	30kW, 4 Poles, Frame Size 200, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB3/IM1001 Mounting (3GKP202410-ADK)
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Output Power	30 kW
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Depth / Length	824 mm
Product Net Height	573 mm
Product Net Weight	347 kg
Product Net Width	392 mm
Product Type	3KP3_M3KP_IE3_Flameproof_Exde_motor
Quote Only	No
Selling Unit of Measure	piece
Short Description	30kW, 4P, Frame Size 200, 3PH, 400V, 50Hz, IP55, IMB3/IM1001
Standards	IEC 60034-1
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors

