

---

PRODUCT-DETAILS

# 3GKP203420-BDL

## M3KP 200MLB 6



---

### General Information

Product ID	3GKP203420-BDL
ABB Type Designation	M3KP 200MLB 6
Catalog Description	M3KP 200MLB 6

---

### Additional Information

ABB Type Designation	M3KP 200MLB 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6312/C3
Bearing NDE	6310/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
EX-Protection	Exde
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	22.00 kW	989 r/min	24.60 A	0.810	92.20 %	212.40 N·m	7.30
D	T4	50 Hz	400 V	22.00 kW	989 r/min	42.40 A	0.810	92.20 %	212.40 N·m	7.30
D	T4	50 Hz	415 V	22.00 kW	990 r/min	41.90 A	0.790	92.20 %	212.20 N·m	7.80
D	T4	60 Hz	440 V	22.00 kW	1190 r/min	38.10 A	0.820	93.00 %	176.60 N·m	7.60
D	T4	60 Hz	460 V	22.00 kW	1191 r/min	36.70 A	0.810	93.00 %	176.50 N·m	8.30

Gas Group	IIB
Gross Weight	357 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 92.2 % Partial Load (75%) 92.2 % Partial Load (50%) 91.0 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 93.0 % Partial Load (75%) 92.8 % Partial Load (50%) 91.4 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3KP 200MLB 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	347 kg
Product Type	5KP3__M3KP_IE3_Flameproof_Exde_motor
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

## Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors

