
PRODUCT-DETAILS

3GKP222220-ADK

M3KP 225SMB 4



General Information

Product ID	3GKP222220-ADK
ABB Type Designation	M3KP 225SMB 4
Catalog Description	M3KP 225SMB 4

Additional Information

ABB Type Designation	M3KP 225SMB 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6313/C3
Bearing NDE	6312/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
EX-Protection	Exde
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	45.00 kW	1482 r/min	46.50 A	0.850	95.20 %	289.00 N·m	7.90
D	T4	50 Hz	400 V	45.00 kW	1482 r/min	80.20 A	0.850	95.20 %	289.00 N·m	7.90
Y	T4	50 Hz	660 V	45.00 kW	1479 r/min	48.30 A	0.860	94.60 %	289.00 N·m	7.20
D	T4	50 Hz	380 V	45.00 kW	1479 r/min	83.90 A	0.860	94.60 %	289.00 N·m	7.20
D	T4	50 Hz	415 V	45.00 kW	1483 r/min	78.30 A	0.840	95.10 %	289.00 N·m	8.50
D	T4	60 Hz	460 V	45.00 kW	1785 r/min	70.50 A	0.840	95.30 %	240.00 N·m	8.90

Gas Group	IIB
Gross Weight	461 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 94.6 % Partial Load (75%) 95.4 % Partial Load (50%) 95.5 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 95.0 % Partial Load (75%) 95.1 % Partial Load (50%) 94.5 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3KP 225SMB 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	451 kg
Product Type	3KP3_M3KP_IE3_Flameproof_Exde_motor
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors

